

INT-RX-S

433 MHz KEYFOB RECEIVER EXPANSION MODULE

433MHz keyfob receiver permits the use of remote control keyfobs to control the alarm system. It makes the control of a home alarm system as simple as the control of a car alarm.

- enables the use of 433 MHz remote control keyfobs with **INTEGRA, VERSA, PERFECTA 16, PERFECTA 32, PERFECTA 32 LTE, PERFECTA-IP 32, PERFECTA-T 32** panels and **ACCO NET** access system
- full remote control user identification
- flexible assignment of functions to keyfobs' buttons
- compatible with **P-2, P-4, T-1, T-2, T-4, , MPT-300** and **MPT-350** remote control keyfobs
- small enclosure facilitates installation in a suitable place



TECHNICAL DATA

Number of supported remote control keyfobs	248
Supply voltage	12 V DC
Enclosure dimensions	24 x 110 x 27 mm
Operating temperature range	-10 °C...+55 °C
Standby mode current consumption	24 mA
Max. current consumption	29 mA
Weight	30 g
Maximum humidity	93±3%
Environmental class according to EN50130-5	II
Supported keyfobs	MPT-300, P-2, P-4, T-1, T-2, T-4
Keyfob operating frequency band	433,05 ÷ 434,79 MHz